



---

DATE: 9 February, 2017

PCN #: 2248

PCN Title: Lead Frame Supplier Change and Datasheet Change for High Level Gate Driver Output Voltage Minimum and Typical Values on Select Analog Automotive Parts

Dear Customer:

This is an announcement of change(s) to products that are currently being offered by Diodes Incorporated.

We request that you acknowledge receipt of this notification within 30 days of the date of this PCN. If you require samples for evaluation purposes, please make a request within 30 days as well. Otherwise, samples may not be built prior to this change. Please refer to the implementation date of this change as it is stated in the attached PCN form. Please contact your local Diodes sales representative to acknowledge receipt of this PCN and for any sample requests.

The changes announced in this PCN will not be implemented earlier than 90 days from the notification date stated in the attached PCN form.

Previously agreed upon customer specific change process requirements or device specific requirements will be addressed separately.

For questions or clarification regarding this PCN, please contact your local Diodes sales representative.

Sincerely,

Diodes Incorporated PCN Team



---

**PRODUCT CHANGE NOTICE****PCN-2248 REV 00**

---

<b>Notification Date:</b>	<b>Implementation Date:</b>	<b>Product Family:</b>	<b>Change Type:</b>	<b>PCN #:</b>
9 February, 2017	9 May, 2017	Analog - Automotive	Lead Frame Supplier and Datasheet change	<b>2248</b>
<b>TITLE</b>				
Lead Frame Supplier Change and Datasheet Change for High Level Gate Driver Output Voltage Minimum and Typical Values on Select Analog Automotive Parts				
<b>DESCRIPTION OF CHANGE</b>				
<p>This PCN is being issued to notify customers that in order to assure continuity of supply, Diodes has qualified lead frames from supplier ASM for below listed products. The current supplier of lead frames will cease production. The base material, dimensions and plating of the lead frame are not changing.</p> <p>Additionally a change will be made to the ZXLD1371QESTTC datasheet as follows: Change of VGateH min limit from 10V to 9.5V @ 12V Vin. See Figures 1 &amp; 2 on the following page.</p> <p>Figure 1: Current Datasheet – Electrical Conditions for ZXLD1371QESTTC Figure 2: Updated Datasheet – Electrical Conditions for ZXLD1371QESTTC</p> <p>Full electrical characterization and high reliability testing has been completed on representative part numbers using lead frames from ASM.</p> <p>There will be no change to the Form or Fit of affected products.</p>				
<b>IMPACT</b>				
Part Numbers Affected: ZXLD1370QESTTC – Lead Frame Supplier Change ZXLD1371QESTTC - Lead Frame Supplier Change and Datasheet Change				
<b>PRODUCTS AFFECTED</b>				
ZXLD1370QESTTC, ZXLD1371QESTTC				
<b>WEB LINKS</b>				
<b>Manufacturer's Notice:</b>	<a href="http://www.diodes.com/pcns">http://www.diodes.com/pcns</a>			
<b>For More Information Contact:</b>	<a href="http://www.diodes.com/contacts.html">http://www.diodes.com/contacts.html</a>			
<b>Data Sheet:</b>	<a href="http://www.diodes.com/catalog">http://www.diodes.com/catalog</a>			
<b>DISCLAIMER</b>				
<b>Unless a Diodes Incorporated Sales representative is contacted in writing within 30 days of the posting of this notice, all changes described in this announcement are considered approved.</b>				

**Figure 1: Current Datasheet – Electrical Characteristics for ZXLD1371QESTTC**

**Electrical Characteristics (cont.) (Test conditions:  $V_{IN} = V_{AUX} = 12V$ ,  $T_A = 25^{\circ}C$ , unless otherwise specified.)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>Driver output (PIN GATE)</b>						
$V_{GATEH}$	High level output voltage	No load Sourcing 1mA (Note 12)	10	11		V

**Figure 2: Updated Datasheet – Electrical Characteristics for ZXLD1371QESTTC**

$V_{GATEH}$	High level output voltage	No load Sourcing 1mA (Note 15)	$V_{IN} = V_{AUX} = 12V$	9.5	10.5	—	V
-------------	---------------------------	--------------------------------	--------------------------	-----	------	---	---